



Kroon-Oil Gear Oils

ATF Dexron II-D

Description

ATF Dexron II-D is an extremely high graded Automatic Transmission Fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- Very high and stable viscosity index
- Very low Pour Point
- Excellent stability against oxidation
- Positive activity against wear, corrosion and foaming
- Specific friction properties
- Perfect compatibility with seal and non-ferro metals

Application

ATF Dexron II-D may be used for automatic gear-boxes, power-steering, torque converters and other equipment, for which an ATF Dexron 2-D fluid is required.

Specifications

GM Dexron IID
Allison C-3/C-4
MB-Approval 236.7
MAN 339 Type Z-1
ZF TE-ML-03D/04D/11A/14A/17C
Ford SQM-2C9010-B
Voith
Caterpillar TO-2
Renk
Ford M2C138-CJ/166-H/185-A
Mercon

Typical standard analyses

| | |
|--------------------------------------|-------|
| Density at 15 °C, kg/l | 0,868 |
| Viscosity 40 °C, mm ² /s | 43,20 |
| Viscosity 100 °C, mm ² /s | 8,25 |
| Viscosity Index | 168 |
| Flash Point COC, °C | 198 |
| Pour Point, °C | -45 |
| Total Base Number, mgKOH/g | 2,6 |
| Sulphate Ash, % | 0,18 |

11/08/2010

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.