

INPA - Loader: E60 Version 1.09

About...

Read error memory

ERROR MEMORY

Date: 16.08.2014 11:24:39
Model: E60
Scope: all control module
JobStatus: OKAY
Quantity: 32

ADR	Gen.	name	JobStatus	Number of errors
00	ZGM		OKAY	No Error stored
01	SIM/SGM		OKAY	No Error stored
02	SZL		OKAY	No Error stored
05	STUL/TEFA		OKAY	No Error stored
06	STUR/TEBF		OKAY	No Error stored
0E	SFZ		OKAY	No Error stored
12	DHE/DDE		OKAY	2 Error stored
		3F57		04
		4185		51
17	EKP		OKAY	No Error stored
18	EGS		OKAY	No Error stored
29	DSC		OKAY	No Error stored
38	ENC		OKAY	No Error stored
3F	ASK		OKAY	No Error stored

RUNNING

Error memory

F1 F2 F3 F4 F5 F6 F7 F8 F9 F10

Read EM Clear EM Clear IM Clear HM Funct DTC Print Back

Start 11:25 2014.08.16

INPA - Loader: Engineelectronic DDE50 for H57TUE Version 1.070

About...

Read error memory

ERROR MEMORY

Date: 16.08.2014 11:27:34
ECU: D50H57E0
JobStatus: OKAY
Variant: D50H57E0

RESULT: 2 error in error memory !

3F57 3F57 (1272) manifold pressure actuator

Error counter: 1
Logistic counter: 40

Mileage	162408	km
Engine speed	2868.57	1/min
coolant temperature	85.26	°C
Rail pressure Actual	1402.13	bar
Injection quantity	58.68	mg/Hub
Air mass per cylinder	1808.26	mg/Hub
Charge pressure Actualwert	2244.91	mbar
Linearised APP1	96.86	%
Battery Voltage	14011.66	mV
Vehicle speed	150.02	km/h
duty cycle manifold pressure actuator	64.59	%

Ladedrucksteller elektrisch oder mechanisch defekt oder Uebertemperatur
Test conditions fulfilled
Error not occurred yet
Error would not cause a warning lamp to light up
Fehler in Entprellphase
Fehler in Entprellphase
Fehler in Entprellphase

RUNNING

Error memory

F1 F2 F3 F4 F5 F6 F7 F8 F9 F10

Read EM Clear EM Read IM Clear IM Print IM Print EM Back

Start 11:29 2014.08.16

INPA - Loader: Engineelectronic DDE50 for M57TUE Version 1.070
About...

Read error memory

Error code: 3F 57 04 02 00 00 01 28 4F 4D 68 87 02 95 A0 E4
7A 56 98 52

4185 4185 Exhaust temperatue sensor vor Kat, Signal

Error counter: 1
Logistic counter: 40

Mileage	162416	km
Engine speed	4358.02	1/min
coolant temperature	99.32	°C
Rail pressure Actual	1591.18	bar
Injection quantity	47.65	mg/Hub
Air mass per cylinder	825.51	mg/Hub
Charge pressure Actualwert	2195.68	mbar
exhaust temperature in front of oxidation catalyst	759.20	°C
exhaust temperatur in front of particle filter	502.78	°C
Intake air temperature	27.03	°C
Environment pressure	994.46	mbar

Signal zu hoch
Test conditions not yet fulfilled
Error present now, but not yet stored (debouncing phase)
Error would not cause a warning lamp to light up
Fehler in Entprellphase
Fehler in Entprellphase
Fehler in Entprellphase

Error code: 41 85 51 02 00 00 01 28 4F 4E 9E 95 CA 79 83 DF
F3 A6 AD 65

RUNNING

Error memory

F1	F2	F3	F4	F5	F6	F7	F8	F9	F10
Read EM	Clear EM	Read IM	Clear IM				Print IM	Print EM	Back

Start | [Icons] | BMW_programos » EN | 11:29 | 2014.08.16